

Log Structured File Systems

Motivating Observations

- Memory size is growing at a rapid rate
- ⇒ Growing proportion of file system reads will be satisfied by file system buffer cache
- ⇒ Writes will increasingly dominate reads

Motivating Observations

- Creation/Modification/Deletion of small files form the majority of a typical workload
- Workload poorly supported by traditional Inode-based file system (e.g. BSD FFS, ext2fs)
 - Example: create 1k file results in: 2 writes to the file inode, 1 write to data block, 1 write to directory data block, 1 write to directory inode
 - ⇒ 5 small writes scattered within group
 - Synchronous writes (write-through caching) of metadata and directories make it worse
 - Each operation will wait for disk write to complete.
- Write performance of small files dominated by cost of metadata writes


Super Block	Group Descriptors	Data Block Bitmap	Inode Bitmap	Inode Table	Data blocks
-------------	-------------------	-------------------	--------------	-------------	-------------

Motivating Observations

- Consistency checking required for ungraceful shutdown due to potential for sequence of updates to have only partially completed.
- File system consistency checkers are time consuming for large disks.
- Unsatisfactory boot times where consistency checking is required.



Basic Idea!!!

- Buffer sequence of updates in memory and write all updates sequentially to disk in one go.




Issues

- How do we now find I-nodes that are scattered around the disk?
- ⇒ Keep a map of inode locations
 - Inode map is also “logged”
 - Assumption is I-node map is heavily cached and rarely results in extra disk accesses
 - To find block in the I-node map, use two fixed location on the disk contains address of block of the inode map
 - Two copies of the inode map addresses so we can recover if error during updating map.



LFS versus FFS

- Comparison of creating two small files




Issue Disks are Finite in Size

- File system “cleaner” runs in background
 - Recovers blocks that are no longer in use by consulting current inode map
 - Identifies unreachable blocks
 - Compacts remaining blocks on disk to form contiguous segments for improved write performance

Issue Recovery

- File system is check-pointed regularly which saves
 - A pointer to the current head of the log
 - The current Inode Map blocks
- On recovery, simply restart from previous checkpoint.
 - Can scan forward in log and recover any updates written after previous checkpoint
 - Write updates to log (no update in place), so previous checkpoint always consistent




Reliability

- Updated data is written to the log, not in place.
- Reduces chance of corrupting existing data.
 - Old data in log always safe.
 - Crashes only affect recent data
 - As opposed to updating (and corrupting) the root directory.

Performance

- Comparison between LFS and SunOS FS
 - Create 10000 1K files
 - Read them (in order)
 - Delete them
- Order of magnitude improvement in performance for small writes



LFS not a clear winner

- When LFS cleaner overhead is ignored, and FFS runs on a new, unfragmented file system, each file system has regions of performance dominance.
 - LFS is an order of magnitude faster on small file creates and deletes.
 - The systems are comparable on creates of large files (one-half megabyte or more).
 - The systems are comparable on reads of files less than 64 kilobytes.
 - LFS read performance is superior between 64 kilobytes and four megabytes, after which FFS is comparable.
 - LFS write performance is superior for files of 256 kilobytes or less.
 - FFS write performance is superior for files larger than 256 kilobytes.
- Cleaning overhead can degrade LFS performance by more than 34% in a transaction processing environment. Fragmentation can degrade FFS performance, over a two to three year period, by at most 15% in most environments but by as much as 30% in file systems such as a news partition.

Margo Seltzer and Keith A. Smith and Hari Balakrishnan and Jacqueline Chang and
Sara Momains and Venkata Padmanabhan

"File System Logging Versus Clustering: A Performance Comparison"

Journaling file systems

- Hybrid of
 - I-node based file system
 - Log structured file system (journal)
- Many variations
 - log only meta-data to journal
 - log-all to journal
- Need to write-twice (i.e. copy from journal to i-node based files)
- Example – ext3