Case study: ext2 FS THE UNIVERSITY OF REW SOUTH WALES

The ext2 file system

- Second Extended Filesystem
 - The main Linux FS before ext3
 - Evolved from Minix filesystem (via "Extended Filesystem")
- Features
 - Block size (1024, 2048, and 4096) configured at FS creation
 - inode-based FS
 - Performance optimisations to improve locality (from BSD FES)
- Main Problem: unclean unmount →e2fsck
 - Ext3fs keeps a journal of (meta-data) updates
 - Journal is a file where updates are logged
 - Compatible with ext2fs




Recap: i-nodes

- · Each file is represented by an inode on disk
- · Inode contains all of a file's metadata
 - Access rights, owner, accounting info
 - (partial) block index table of a file
- Each inode has a unique number
 - System oriented name
 - Try 'ls -i' on Unix (Linux)
- · Directories map file names to inode numbers
 - Map human-oriented to system-oriented names





3





mode uid gid atime ctime mtime size block count reference count direct blocks (12) single indirect double indirect	Ext2 i-nodes • Mode - Type • Regular file or directory - Access mode • rwxrwxrwx • Uid - User ID • Gid - Group ID			
THE UNIVERSITY OF NEW SOUTH WALES 5				


mode uid gid atime ctime mtime size block count reference count direct blocks (12) single indirect triple indirect	Inode Contents		
THE UNIVERSITY OF NEW SOUTH WALES 6			












Problem • How do we store files greater than 12 blocks in size? - Adding significantly more direct entries in the inode results in many unused entries most of the time.





Single Indirection


- Requires two disk access to read
 - One for the indirect block; one for the target block
- · Max File Size
 - Assume 1Kbyte block size, 4 byte block numbers 12 * 1K + 1K/4 * 1K = 268 KiB
- For large majority of files (< 268 KiB), given the inode, only one or two further accesses required to read any block in file.



14







Max File Size


- Assume 4 bytes block numbers and 1K blocks
- The number of addressable blocks
 - Direct Blocks = 12
 - Single Indirect Blocks = 256
 - Double Indirect Blocks = 256 * 256 = 65536
 - Triple Indirect Blocks = 256 * 256 * 256 = 16777216
- Max File Size


12 + 256 + 65536 + 16777216 = 16843020 blocks ≈ 16 GB





18


Where is the data block number stored? • Assume 4K blocks, 4 byte block numbers, 12 direct blocks • A 1 byte file produced by - Iseek(fd, 1048576, SEEK_SET) /* 1 megabyte */ - write(fd, "x", 1) • What if we add - Iseek(fd, 5242880, SEEK_SET) /* 5 megabytes */ - write(fd, "x", 1)














Some Best and Worst Case Access Patterns

Assume Inode already in memory

- · To read 1 byte
 - Best:
 - 1 access via direct block
 - Worst:
 - · 4 accesses via the triple indirect block
- · To write 1 byte
 - Best:
 - 1 write via direct block (with no previous content)
 - Worst:
 - 4 reads (to get previous contents of block via triple indirect) + 1 write (to write modified block back)



26

Worst Case Access Patterns with Unallocated Indirect Blocks

- · Worst to write 1 byte
 - 4 writes (3 indirect blocks: 1 data)
 - 1 read, 4 writes (read-write 1 indirect, write 2; write 1 data)
 - 2 reads, 3 writes (read 1 indirect, read-write 1 indirect, write 1; write 1 data)
 - 3 reads, 2 writes (read 2, read-write 1; write 1 data)
- · Worst to read 1 byte
 - If reading writes a zero-filled block on disk
 - Worst case is same as write 1 byte
 - If not, worst-case depends on how deep is the current indirect block tree.



27

Inode Summary

- •The inode contains the on disk data associated with a file
- -Contains mode, owner, and other bookkeeping
- -Efficient random and sequential access via indexed allocation
- -Small files (the majority of files) require only a single access
- -Larger files require progressively more disk accesses for random access
- •Sequential access is still efficient
- -Can support really large files via increasing levels of indirection



28

Where/How are Inodes Stored

Boot Super Inode Block Block Array Data Blocks

- System V Disk Layout (s5fs)
 - Boot Block
 - contain code to bootstrap the OS
 - Super Block
 - · Contains attributes of the file system itself
 - e.g. size, number of inodes, start block of inode array, start of data block area, free inode list, free data block list
 - Inode Array
 - Data blocks



29

Some problems with s5fs

- · Inodes at start of disk; data blocks end
 - Long seek times
 - Must read inode before reading data blocks
- · Only one superblock
 - Corrupt the superblock and entire file system is lost
- · Block allocation was suboptimal
 - Consecutive free block list created at FS format time
 - Allocation and de-allocation eventually randomises the list resulting in random allocation
- · Inodes also allocated randomly
 - Directory listing resulted in random inode access patterns




30



- ·Historically followed s5fs
- -Addressed many limitations with s5fs
- -ext2fs mostly similar



31



- •Partition:
- -Reserved boot block,
- -Collection of equally sized block groups
- -All block groups have the same structure



32

Layout of a Block Group



- •Replicated super block
- -For e2fsck
- Group descriptors
- •Bitmaps identify used inodes/blocks
- •All block groups have the same number of data blocks
- •Advantages of this structure:
- Replication simplifies recovery
 Proximity of inode tables and data blocks (reduces seek time)



33

Superblocks

- ·Size of the file system, block size and similar parameters
- •Overall free inode and block counters
- •Data indicating whether file system check is needed:
- -Uncleanly unmounted
- -Inconsistency
- -Certain number of mounts since last check
- -Certain time expired since last check
- •Replicated to provide redundancy to aid recoverability



34

Group Descriptors


- Location of the bitmaps
- •Counter for free blocks and inodes in this group
- •Number of directories in the group





Performance considerations


- EXT2 optimisations
 - Block groups cluster related inodes and data blocks
- -Pre-allocation of blocks on write (up to 8 blocks)
- •8 bits in bit tables
- •Better contiguity when there are concurrent writes
- -Aim to store files within a directory in the same group


















Symbolic links


- A symbolic link is a file that contains a reference to another file or directory
 - Has its own inode and data block, which contains a path to the target file
 - Marked by a special file attribute
 - Transparent for some operations
 - Can point across FS boundaries








•Deleting a filename -rm file2 •Adjust the record length to skip to next valid entry The LINIVERSITY OF RW SOUTH WALES Inode No Rec Length Name Length Name Length Name | 12 | 2 | 17 | 13 | 10 | 2 | The LINIVERSITY OF RW SOUTH WALES

PS reliability Disk writes are buffered in RAM OS crash or power outage ==> lost data Commit writes to disk periodically (e.g., every 30 sec) Use the sync command to force a FS flush FS operations are non-atomic Incomplete transaction can leave the FS in an inconsistent state









FS reliability

- e2fsck
 - Scans the disk after an unclean shutdown and attempts to restore FS invariants
- · Journaling file systems
 - Keep a journal of FS updates
 - Before performing an atomic update sequence,
 - write it to the journal
 - Replay the last journal entries upon an unclean shutdown
 - Example: ext3fs

