

What is Scheduling?

- On a multi-programmed system
 - We may have more than one Ready process
- On a batch system
 - We may have many jobs waiting to be run
- On a multi-user system
 - We may have many users concurrently using the system
- The *scheduler* decides who to run next.
 - The process of choosing is called *scheduling*.



3

Is scheduling important?

- · It is not in certain scenarios
 - If you have no choice
 - · Early systems
 - Usually batching
 - Scheduling algorithm simple
 - » Run next on tape or next on punch tape
 - Only one thing to run
 - Simple PCs
 - Only ran a word processor, etc....
 - Simple Embedded Systems
 - TV remote control, washing machine, etc....



4


Is scheduling important?

- · It is in most realistic scenarios
 - Multitasking/Multi-user System
 - Example
 - Email daemon takes 2 seconds to process an email
 - Email daemon takes 2 seconds to
 User clicks button on application.
 - Scenario 1
 - Run daemon, then application
 - » System appears really sluggish to the user
 - Scenario 2
 - Run application, then daemon
 - Application appears really responsive, small email delay is unnoticed
- Scheduling decisions can have a dramatic effect on the perceived performance of the system
 - Can also affect correctness of a system with deadlines



_


Application Behaviour





Bursts of CPU usage alternate with periods of I/O wait





ь














Preemptive versus Non-preemptive Scheduling

- · Non-preemptive
 - Once a thread is in the *running* state, it continues until it completes, blocks on I/O, or voluntarily yields the CPU
 - A single process can monopolised the entire system
- · Preemptive Scheduling
 - Current thread can be interrupted by OS and moved to ready state
 - Usually after a timer interrupt and process has exceeded its maximum run time
 - Can also be as a result of higher priority process that has become ready (after I/O interrupt).
 - Ensures fairer service as single thread can't monopolise the system
 - · Requires a timer interrupt



. . .

Categories of Scheduling Algorithms

- The choice of scheduling algorithm depends on the goals of the application (or the operating system)
 - No one algorithm suits all environments
- We can roughly categorise scheduling algorithms as follows
 - Batch Systems
 - No users directly waiting, can optimise for overall machine performance
 - Interactive Systems
 - Users directly waiting for their results, can optimise for users perceived performance
 - Realtime Systems
 - Jobs have deadlines, must schedule such that all jobs (mostly) meet their deadlines.



14

Goals of Scheduling Algorithms

- · All Algorithms
 - Fairness
 - Give each process a fair share of the CPU
 - Policy Enforcement
 - What ever policy chosen, the scheduler should ensure it is carried out
 - Balance/Efficiency
 - Try to keep all parts of the system busy



15

Goals of Scheduling Algorithms

- · Interactive Algorithms
 - Minimise response time
 - Response time is the time difference between issuing a command and getting the result
 - E.g selecting a menu, and getting the result of that selection
 - Response time is important to the user's perception of the performance of the system.
 - Provide Proportionality
 - Proportionality is the user expectation that short jobs will have a short response time, and long jobs can have a long response time.
 - · Generally, favour short jobs



16

Goals of Scheduling Algorithms

- · Real-time Algorithms
 - Must meet deadlines
 - Each job/task has a deadline.
 - A missed deadline can result in data loss or catastrophic failure
 - Aircraft control system missed deadline to apply brakes
 - Provide Predictability
 - For some apps, an occasional missed deadline is okay
 - E.g. DVD decoder
 - Predictable behaviour allows smooth DVD decoding with only rare skips



17

Interactive Scheduling





Round Robin Scheduling


- Each process is given a timeslice to run in
- When the timeslice expires, the next process preempts the current process, and runs for its timeslice, and so on
 - The preempted process is placed at the end of the queue
- · Implemented with
 - A ready queue
 - A regular timer interrupt



19







Round Robin

- Pros
- Fair, easy to implement
- Con
 - Assumes everybody is equal
- · Issue: What should the timeslice be?
 - Too short
 - · Waste a lot of time switching between processes
 - Example: timeslice of 4ms with 1 ms context switch = 20% round robin overhead
 - Too long
 - System is not responsive
 - Example: timeslice of 100ms
 - If 10 people hit "enter" key simultaneously, the last guy to run will only see progress after 1 second.
 - Degenerates into FCFS if timeslice longer than burst length





23


Priorities


- Each Process (or thread) is associated with a priority
- Provides basic mechanism to influence a scheduler decision:
 - Scheduler will always chooses a thread of higher priority over lower priority
- · Priorities can be defined internally or externally
 - Internal: e.g. I/O bound or CPU bound
 - External: e.g. based on importance to the user









































































Traditional UNIX Scheduler The highest priority (lower number) is scheduled Priorities are re-calculated once per second, and re-inserted in appropriate queue Avoid starvation of low priority threads Penalise CPU-bound threads Penalise CPU-bound threads THE UNIVERSITY OF NEW SOUTH WALLS







Real Time System (RTS)

- RTS accepts an activity A and guarantees its requested (timely) behaviour B if and only if
 - RTS finds a schedule
 - that includes all already accepted activities Ai and the new activity A,
 - that guarantees all requested timely behaviour Bi and B, and
 - that can be enforced by the RTS.
- · Otherwise, RT system rejects the new activity A.



53

Typical Real Time Systems

- Control of laboratory experiments
- Robotics
- (Air) Traffic control
- Controlling Cars / Trains/ Planes
- Telecommunications
- Medical support (Remote Surgery, Emergency room)
- Multi-Media
- Remark: Some applications may have only soft-real time requirements, but some have really hard real-time requirements



Hard-Real Time Systems

- · Requirements:
 - Must always meet all deadlines (time guarantees)
 - You have to guarantee that in any situation these applications are done in time, otherwise dangerous things may happen

Examples:

- If the landing of a fly-by-wire jet cannot react to sudden side-winds within some milliseconds, an accident might occur.
- An airbag system or the ABS has to react within milliseconds



55

Soft-Real Time Systems

Requirements:

Must mostly meet all deadlines, e.g. 99.9% of cases Examples:

- Multi-media: 100 frames per day might be dropped (late)
- 2. Car navigation: 5 late announcements per week are acceptable
- 3. Washing machine: washing 10 sec over time might occur once in 10 runs, 50 sec once in 100 runs.



56

Predictability, not Speed


- Real time systems are NOT necessarily fast
- Real time systems can be slow, as long as they are predictably so.
 - It does not matter how fast they are, as long as they meet their deadlines.



57

Properties of Real-Time Tasks

- To schedule a real time task, its properties must be known *a priori*
- The most relevant properties are
 - Arrival time (or release time) a_i
 - Maximum execution time (service time)
 - Deadline d_i



Categories of Real time tasks

- · Periodic
 - Each task is repeated at a regular interval
 - Max execution time is the same each period
 - Arrival time is usually the start of the period
 - Deadline is usually the end
- · Aperiodic (and sporadic)
 - Each task can arrive at any time



59

Real-time scheduling approaches

- · Static table-driven scheduling
 - Given a set of tasks and their properties, a schedule (table) is precomputed offline.
 - Used for periodic task set
 - Requires entire schedule to be recomputed if we need to change the task set
- · Static priority-driven scheduling
 - Given a set of tasks and their properties, each task is assigned a fixed priority
 - A preemptive priority-driven scheduler used in conjunction with the assigned priorities
 - Used for periodic task sets




Real-time scheduling approaches

- · Dynamic scheduling
 - Task arrives prior to execution
 - The scheduler determines whether the new task can be admitted
 - Can all other admitted tasks and the new task meet their deadlines?
 - If no, reject the new task
 - Can handle both periodic and aperiodic tasks



61

THE UNIVERSITY OF NEW SOUTH WALES




Two Typical Real-time Scheduling Algorithms

- · Rate Monotonic Scheduling
 - Static Priority priority-driven scheduling
 - Priorities are assigned based on the period of each task
 - The shorter the period, the higher the priority
- · Earliest Deadline First Scheduling
 - The task with the earliest deadline is chosen next



63




Is the Example Schedulable


$$\sum_{i=1}^{m} \frac{C_i}{P_i} \le 1$$

$$\frac{10}{30} + \frac{15}{40} + \frac{5}{50} = 0.808$$

YES










Let's Modify the Example Slightly

- Increase A's CPU requirement to 15 msec
- The system is still schedulable

$$\frac{15}{30} + \frac{15}{40} + \frac{5}{50} = 0.975$$







RMS failed, why?

- It has been proven that RMS is only guaranteed to work if the CPU utilisation is not too high
 - For three tasks, CPU utilisation must be less than 0.780
 - We were lucky with our original example

$$\sum_{i=1}^{m} \frac{C_i}{P_i} \le m(2^{\frac{1}{m}} - 1)$$



71

EDF

- EDF always works for any schedulable set of tasks, i.e. up to 100% CPU utilisation
- Summary
 - If CPU utilisation is low (usual case, due to safety factor in estimating execution times)
 - Can use RMS which is simple and easy to implement
 - If CPU utilisation is high
 - Must use EDF

